



Spec Sheet

QTscu 4005

QT Sound Insulation is a high-quality sound control underlayment manufactured in the USA. QT is backed by hundreds of acoustical tests and a team of acoustical engineers to help you provide the right acoustic solution.



Dimensions

- 5mm(1/4"); 48" x 30 LF
- 0.84 lb/ft²
- Standard Tolerances: Width: $\pm 1/2"$ - $1/4"$, Length: + 1% - 0", Thickness: ± 0.4 mm

Performance Attributes

- Applicable for a wide range of flooring types (tile, wood, laminate, LVT, carpet)
- Vapor barrier option available
- Crack isolation membrane (ANSI A118.12) protects ceramic, porcelain and stone tile from substrate cracks
- Commercially rated by the Tile Council of North America
- FloorScore Certified
- Can contribute toward earning up to 9 LEED points
- Supported by over 550 independent lab/field test and a team of acoustical engineers
- Superior long-term acoustical performance-will not degrade over time

Technical Data

Property	Test Method	Typical Results
Density	ASTM D297	60 lb/ft ³
Thickness	ASTM D3676	2mm (0.08")
Tensile Strength	ASTM D412, Die C	180 psi
Compression @100 psi	ASTM F36	20-30%
Shore A Hardness	ASTM D2240	55
Crack Resistance	ANSI 118.12 5.4	High Performance

Acoustics

- IIC 67, STC 62 with engineered wood flooring, 1 layer QTscu 4005, 8" reinforced concrete slab, suspended ceiling(Intertek E3618.02)
- IIC 50, STC 60 with ceramic tile, QTscu 4005, 1" gypsum concrete, TJI joists, resilient channels, ceiling (NGC 501034, 7013055)."

The original recycled rubber impact sound insulation since 2000.

The values shown represent current production based on standard QTscu specs and may vary per thickness. This material has a shelf life of 5 years from date of manufacture when protected from environmental extremes.